C.12. Polychlorinated Biphenyls (PCBs) Controls

The Permittees shall implement the following control program for PCBs. The Permittees shall implement PCBs control measures (source control, treatment control, and pollution prevention strategies) in areas where benefits are most likely to accrue (focused implementation) and report on those control measures according to the provisions below. The provisions implement the urban runoff requirements of the PCBs TMDL. Permittees shall reduce PCBs loads by a specified amount during the term of the permit, thereby making substantial progress toward achieving the urban runoff PCBs wasteload allocation in the Basin Plan. The allocation, on an aggregate and regionwide basis, of 2 kg/yr (representing a load reduction from all urban runoff sources of approximately 18 kg/yr compared to loads estimated using data collected in 2003), is to be achieved by March 2030. The Permittees may comply with any requirement of this Provision through a collaborative effort.

C.12.a. Implement Control Measures to Achieve PCBs Load Reductions.

- i. Task Description Permittees shall implement PCBs source and treatment control measures and pollution prevention strategies to achieve PCBs load reductions in Table 12.1 throughout the area covered by the permit.
- ii. Implementation level -To comply with this provision element, Permittees shall:
 - (1) Identify the watersheds in which PCBs control measures are currently being implemented and those in which new control measures will be implemented during the term of this permit,
 - (2) Identify the control measures that are currently being implemented and those that will be implemented in each watershed, and
 - (3) Submit a schedule of control measure implementation.
 - (4) Implement sufficient control measures to achieve county-specific load reduction performance criteria shown in Table 12.1 and demonstrate achievement of these load reductions by using the accounting methods described in the Permit Fact Sheet and documented according to provision C.12.b. Load reductions from control measures implemented prior to the effective date of this permit may be counted toward the required reductions of this permit term if these control measures were established or implemented during the last permit term, but load reductions from the activity were not realized or credited during the last permit term (e.g., they were implemented after the load reduction accounting was submitted).

For all Permittees combined, these county-specific average annual PCBs load reduction performance criteria shall total 0.5 kg/yr during each of the first two years of the permit and 3.0 kg/yr during each of the final three years of the permit. The 0.5 kg/yr reduction (and county-specific portions thereof) shall be assessed for compliance at the end of year 2 and shall be computed as the average of the year 1 and year 2 load reduction. Similarly, the 3.0 kg/yr reduction (and county-specific portions thereof) shall be computed as the average of years 3-5 and shall be assessed for compliance at the end of year 4

(year 5 load reductions will be estimated according to the predicted benefit of control measures which Permittees commit to implement in year 5). The Permit Fact Sheet stipulates the amount of PCBs load reduction benefit associated with a unit of activity for a number of control measures. Permittees will be in compliance with the numeric load reduction performance criteria if they implement sufficient control measures such that the total stipulated benefit of the control measures actually implemented equals or exceeds the numeric load reduction performance criteria shown in Table 12.1 below.

The Countywide Urban Runoff Programs are responsible for specific portions of the Permit-wide load reduction shown in Table 12.1. These county-specific load reduction performance criteria allocate responsibility for load reductions to individual county programs according to the same proportions used to establish county-specific wasteload allocations (and corresponding load reductions) in the PCBs TMDL.

Load reduction opportunities will likely vary by jurisdiction. Some jurisdictions (e.g., those with a higher proportion of old industrial land use) may have more PCBs-contaminated sites, and hence, greater potential opportunities to implement control measures to reduce loads. Further, the total PCBs load reduction across the entire area covered under this permit is relevant to the recovery of San Francisco Bay Therefore, all Permittees will be in compliance with the load reduction performance criteria as long as the total load reductions for the entire area covered by this permit (500 g/yr for years 1-2 and 3 kg/yr for years 3-5) are achieved.

If the area-wide total load reduction criteria (i.e., 500 g/yr and 3000 g/yr) are not achieved, the Permittees in counties meeting the county-level load reduction criteria from Table 12.1 will be deemed in compliance with this Provision. If neither the area-wide total load reduction criteria nor the county-specific load reduction criteria are achieved, those Permittees will be deemed in compliance if they have achieved load reductions consistent with their appropriate proportion of the county total. Permittees shall report on their method for assigning Permittee-specific load fractions by April 2016 (see C.12.b(1) below). As a default, the Permittee share of the county load reduction performance criteria will be allocated by the proportion of county population in each municipality.

Table 12.1 PCBs Load Reductions Performance Criteria by County

County Program	PCBs load reduction (g/yr) during first two years of permit	PCBs Load Reduction (g/yr) for final 3 years of permit
Alameda	160	940
Contra Costa	90	560
San Mateo	60	370
Santa Clara	160	940
Suisun City, Vallejo, Fairfield		190
Totals	500	3000

iii. Reporting

- (1) The Permittees shall report by February 1, 2016 a list of the watersheds (or portions therein) where PCBs control measures are currently being implemented and those in which control measures will be implemented (C.12.a.ii(1)) during the term of this permit as well as the monitoring data and other information used to select these watersheds. This list should include watersheds containing contaminated sites referred to the Water Board as well.
- (2) The Permittees shall report in their 2016 Annual Report the specific control measures (C.12.a.ii(2)) that are currently being implemented and those that will be implemented in watersheds identified under C.12.a.iii(1) and an implementation schedule (C.12.a ii(3)) for these control measures. This report shall include:
 - a. The number, type, and locations and/or frequency (if applicable) of control measures;
 - b. The identity and description of the contaminated sites referred to the Water Board during permit term;
 - c. The description, scope, and start date, of pollution prevention measures;
 - d. For each structural control and non-structural BMP, interim implementation progress milestones (e.g., construction milestones for structural controls or other relevant implementation milestones for structural controls and non-structural BMPs) and a schedule for milestone achievement; and
 - e. Clear statements of the roles and responsibilities of each participating Permittee for implementation of pollution prevention or control measures identified under C.12.a.iii(1).
- (3) Beginning with the 2017 Annual Report and continuing in all Annual Reports, Permittees shall update all the information required under C.12.a iii(2) as necessary to account for new control measures implemented but not described in the 2016 Annual Report.

C.12.b. Assess PCB Load Reductions from Stormwater

i. Task Description – The Permittees shall develop, document, and implement an assessment methodology and data collection program to quantify PCBs loads reduced through implementation of any and all pollution prevention, source control and treatment control efforts required by the provisions of this permit or load reductions achieved through other relevant efforts not explicitly required by the provisions of this permit. The Permittees shall use the assessment methodology to demonstrate progress toward the interim load reduction milestones to be achieved during the term of the permit and demonstrate progress toward attainment of the program area allocations. A reasonable foundation for the load reduction accounting system is described in the Fact Sheet and is based on information submitted by Permittees in December 2013 in

the Integrated Monitoring Report for the previous permit. This task element consists of documenting the approach described in the Fact Sheet, updating and refining the accounting system to account for new information, justifying assumptions and selected parameters used to quantify the load reduction benefit for each type of control measure, and indicating what information will be collected and submitted to confirm the load reduction benefit for each unit of activity.

ii. Implementation Level – The Permittees shall adequately quantify the PCBs load reductions achieved through implementing pollution prevention, source control, and treatment control efforts.

iii. Reporting

(1) The Permittees shall submit, by April 1, 2016, a full description of an adequate measurement and estimation methodology and rationale for the approaches used to assess PCBs load reductions achieved through PCBs source control, stormwater treatment, green infrastructure projects, and other stormwater management measures implemented during the term of this permit. This methodology shall justify the choices for parameters used to estimate load reduction benefits and identify the data that will be collected and submitted in support of any claim of load reduction benefit associated with implemented control measures.

For control measures that become operational at any time during year 5 of the permit term, the estimated load reduction credited to the Permittee for this control measure shall be the estimated PCBs load removed during one full year of operation. For control measures requiring construction or installation of new infrastructure that are under construction but not fully operational as of the end of the permit term, one-half (50%) of the estimated PCBs yearly load reduction shall be counted in year 5 with the remaining 50% load reduction credited during the future year that the infrastructure element is fully operational.

Permittees shall submit Permittee-specific proportions of load reduction responsibilities and supporting data. This can be determined by the counties and may be different from one county to the next. Examples of bases that could be used to determine Permittee-specific load reduction responsibility include the Permittee's proportion of county population or of total county industrial land use.

(2) Beginning with the 2016 Annual Report, Permittees shall report annually the loads reduced using the approved estimation methodology to demonstrate cumulative PCBs load reduced from each control measure implemented since the beginning of permit term. Permittees shall submit all supporting data and information necessary to substantiate the load reduction estimates, including appropriate reference to the control measures described in the reporting required under C.12.a.

(3) In their 2018 and subsequent Annual Reports the Permittees shall submit, for Executive Officer approval, any refinements, if necessary, to the measurement and estimation methodologies to assess PCBs load reductions in the subsequent permit.

C.12.c. Plan and Implement Green Infrastructure to reduce PCBs loads

i. Task Description – Permittees shall implement green infrastructure projects during the term of the permit to achieve PCBs load reductions of 120 g/year over the final three years of the permit term. Additionally, Permittees shall prepare a reasonable assurance analysis (see below and Fact Sheet) to demonstrate quantitatively that PCBs load reductions of at least 3 kg/yr throughout the Permit area will be achieved by 2040 through implementation of green infrastructure plans required by Provision C.3.j.

ii. Implementation Level

(1) Permittees shall implement sufficient green infrastructure projects to achieve county-specific load reduction performance criteria shown in Table 12.2 and demonstrate achievement of these load reductions by using the accounting methods established according to provision C.12.b.ii(1). PCBs load reductions achieved through implementation of green infrastructure may be counted as part of the overall load reductions required during this permit term under C.12.a.ii(4). Load reductions from green infrastructure projects implemented prior to the effective date of this permit may be counted toward the required green infrastructure reductions of this permit term if these projects were established and implemented during the last permit term, but load reductions from the activity were not realized or credited during the last permit term.

For all Permittees combined, these county-specific average annual PCBs load reductions from green infrastructure projects total 120 g/yr during each of the final three years of the permit. The green infrastructure load reduction shall be assessed for compliance at the end of year 4 and shall be computed as the average load reduction of years 3-5 (year 5 load reductions will be estimated according to the predicted benefit of control measures which Permittees commit to implement in year 5).

The Fact Sheet contains land use yield information that allows one to calculate the amount of PCBs load reduction benefit associated with a unit of activity of green infrastructure control measure implementation. Permittees will be in compliance with the numeric load reduction performance criteria if they implement sufficient control measures such that the total stipulated benefit of the control measures actually implemented equals or exceeds the numeric load reduction criteria in Table 12.2. The Countywide Urban Runoff Programs are responsible for the specific portions of these Permit area totals shown in Table 12.2 below.

Green infrastructure implementation opportunities in PCBs-contaminated areas will likely vary by jurisdiction. Therefore, all Permittees will be in compliance with the green infrastructure load reduction performance criteria as long as the total load reduction for the entire area covered by this permit (120 g/yr for years 3-5) is achieved.

If the area-wide total load reduction (i.e.120 g/yr) performance criterion is not achieved, the Permittees in counties meeting the county-level load reduction criteria from Table 12.2 will be deemed in compliance with this Provision. If both the area-wide total load reduction criterion and countyspecific load reduction criterion are not achieved, those Permittees will be deemed in compliance if they have achieved load reductions consistent with their proportion of the county total established under C.12.b.ii(1).

Table 12.2 PCBs Load Reduction Performance Criteria via Green Infrastructure

Implementation by County

County Program	PCBs Load Reduction (g/yr) for final 3 years of permit through green infrastructure
Alameda	37
Contra Costa	23
San Mateo	15
Santa Clara	.37
Suisun City, Vallejo, Fairfield	8
Totals	120

- Permittees shall prepare a reasonable assurance analysis of future PCBs load reductions by doing the following:
 - a. Quantify the relationship between areal extent of green infrastructure implementation and PCBs load reductions, taking into consideration the scale of contamination of the treated area as well as the pollutant removal effectiveness of likely green infrastructure strategies.
 - b. Estimate the amount and characteristics of land area that will be treated through green infrastructure future years 2020, 2030, and 2040.
 - c. Estimate the amount of PCBs load reductions that will result from green infrastructure implementation by future years 2020, 2030, and 2040.
 - d. Quantitatively demonstrate that PCBs reductions of at least 3 kg/yr will be realized by 2040 through implementation of green infrastructure projects.
 - e. Ensure that the calculation methods, models, model inputs and modeling assumptions used to fulfill C.12.c.ii.(2)a.-d. have been validated through a peer review process.

iii. Reporting

- (1) The Permittees shall submit in their 2017 Annual Report, as part of reporting for C.12.b.ii(1), the quantitative relationship between green infrastructure implementation and PCBs load reductions. This submittal shall include all data used and a full description of models and model inputs relied on to establish this relationship.
- (2) The Permittees shall submit in their 2019 Annual Report an estimate of the amount and characteristics of land area that will be treated through green infrastructure implementation by future years 2020, 2030, and 2040. This submittal shall include all data used and a full description of models and model inputs relied on to generate this estimate.
- (3) The Permittees shall submit in their 2019 Annual Report a reasonable assurance analysis to demonstrate quantitatively that PCBs reductions of at least 3 kg/yr will be realized by 2040 through implementation of green infrastructure projects. This submittal shall include all data used and a full description of models and model inputs relied on to make the demonstration and documentation of peer review of the reasonable assurance analysis.
- (4) The Permittees shall submit as part of reporting for C.12.b.ii(2), beginning with their 2019 Annual Report an estimate of the amount of PCBs load reductions resulting from green infrastructure implementation during the term of the permit. This submittal shall include all data used and a full description of models and model inputs relied on to generate this estimate.

C.12.d. Prepare Implementation Plan and Schedule to Achieve TMDL Wasteload Allocations

- i. Task Description Permittees shall prepare a plan and schedule for PCBs control measure implementation and reasonable assurance analysis demonstrating that sufficient control measures will be implemented to attain the PCBs TMDL wasteload allocations by 2030.
- ii. Implementation level Permittees shall prepare a PCBs control measures implementation plan and corresponding reasonable assurance analysis that demonstrates quantitatively that the plan will result in PCBs load reductions sufficient to attain the PCBs TMDL wasteload allocations by 2030. The plan must:
 - (1) Identify all technically and economically feasible PCBs control measures to be implemented (including green infrastructure projects); and
 - (2) Include a schedule according to which these technically and economically feasible control measures will be fully implemented; and
 - (3) Provide an evaluation and quantification of the PCBs load reduction of such measures as well as an evaluation of costs, control measure

efficiency and significant environmental impacts resulting from their implementation.

iii. Reporting

Permittees shall submit the plan and schedule in the 2019 Annual Report.

C.12.e. Evaluate PCBs Presence in Caulks/Sealants Used in Storm Drain or Roadway Infrastructure in Public Rights-of-Way

i. Task Description —Permittees shall collect samples of caulk and other sealants used in storm drains and between concrete curbs and street pavement and investigate whether PCBs are present in such material and in what concentrations. PCBs are most likely present in material applied during the 1970s so the focus of the investigations should be on structures installed during this era.

ii. Implementation Level

Permittees shall collect at least 20 composite samples (throughout the Permit area) of the caulks and sealants used in storm drains or roadway infrastructure in public rights-of-way and analyze this material for PCBs in such a way as to be able to detect a minimum PCBs concentration of 200 parts per billion. This sampling and analysis will count toward partial fulfillment of the monitoring effort aimed at finding PCBs sources (see management information need in C.8.f).

iii. Reporting

Permittees shall report on the results (including all data gathered) of this investigation no later than the 2017 Annual Reports.

C.12.f. Manage PCB-Containing Materials and Wastes During Building Demolition Activities

i. Task Description – Permittees shall develop or cause to be developed a framework for managing PCB-containing materials in applicable structures at the time such structures undergo demolition. Permittees shall implement or cause to be implemented the PCB management framework so that PCBs are not likely to be released off the site during or after demolition through vehicle track-out, airborne releases, soil erosion, or stormwater runoff.

Applicable projects shall include, at a minimum, commercial and industrial structures constructed or remodeled between the years 1950 and 1980. Wood frame structures are exempt.

ii. Implementation Level

(1) During years one, two, and three of the permit term, the Permittees shall develop a framework, to include establishing any necessary authority, for managing PCBs-containing materials in applicable structures at the time such structures undergo demolition. At the start of the fourth year of the permit term and thereafter, the Permittees shall implement or cause to be implemented the PCBs management framework so that PCBs are not likely to be released off the site during or after demolition of applicable structures via vehicle trackout, airborne releases, soil erosion, or stormwater runoff.

iii. Reporting

- (1) In their 2016, 2017, and 2018 Annual Reports, the Permittees shall summarize the steps they have taken to begin implementing this requirement, which could include working with state and local agencies on inter-agency coordination regarding building demolitions, developing ordinances or policies, obtaining information materials, updating or supplementing permit application materials, developing a tracking tool for potential PCB-containing structures, and training relevant staff as needed to comply with this sub-provision.
- (2) Beginning with their 2019 Annual Report and thereafter, the Permittees shall list all applicable structures that have applied for a demolition permit, with the structure's address, project proponent contact information, and dates of permit application and issuance for each project.

C.12.g. Fate and Transport Study of PCBs: Urban Runoff Impact on San Francisco Bay Margins

- i. Task Description The Permittees shall conduct or cause to be conducted studies aimed at better understanding the fate, transport, and biological uptake of PCBs discharged from urban runoff to San Francisco Bay margin areas.
- ii. Implementation Level The specific information needs include understanding the in-Bay transport of PCBs discharged in urban runoff, the sediment and food web PCBs concentrations in margin areas receiving urban runoff, the influence of urban runoff on the patterns of food web PCBs accumulation, especially in Bay margins, and the identification of drainages where urban runoff PCBs are particularly important in food web accumulation.
- iii. Reporting The Permittees shall submit in their 2016 Annual Report a workplan describing the specific manner in which these information needs will be accomplished and describing the studies to be performed with a preliminary schedule. The Permittees shall report on status of the studies in their 2017 Annual Report. The Permittees shall report in the March 15, 2019, Integrated Monitoring Report the findings and results of the studies completed, planned, or in progress as well as implications of studies on potential control measures to be investigated, piloted or implemented in future permit cycles.

C.12.h. Implement a Risk Reduction Program

i. Task Description – The Permittees shall conduct an ongoing risk reduction program to address public health impacts of PCBs in San Francisco Bay/Delta fish. The fish risk reduction program shall take actions to reduce actual and

potential health risks in those people and communities most likely to consume San Francisco Bay-caught fish, such as subsistence fishers and their families. The risk reduction framework developed in the previous permit term, which funded community based organizations to develop and deliver appropriate communications to appropriately targeted individuals and communities, is an appropriate approach. Permittees should work with local health departments, the Bay Area Clean Water Agencies, and the Western States Petroleum Association to leverage resources for this program and to appropriately target at-risk populations.

ii. Implementation Level

- (1) At a minimum, Permittees shall conduct or cause to be conducted an ongoing risk reduction program with the potential to reach 3,000 individuals annually who are likely consumers of San Francisco Baycaught fish. Permittees are encouraged to collaborate with San Francisco Bay industrial and wastewater discharger agencies in meeting this requirement.
- (2) In year four of the permit term, Permittees shall evaluate the effectiveness of their risk reduction program.
- iii. Reporting The Permittees shall report on the status of the risk reduction program in each of their Annual Reports, including a brief description of actions taken, an estimate of the number of people reached, and why these people are deemed likely to consume Bay fish. The Permittees shall report the findings of the effectiveness evaluation of their risk reduction program in their 2019 Annual Report.